




# YC-30

YC-10  
YC-20  
**YC-30**  
YC-40




## ACCESSORIES



Jaw Plate

| WIDTH | LENGTH | TOOTH PITCH |
|-------|--------|-------------|
| 765mm | 965mm  | 56mm        |



Fine Jaw Plate

| WIDTH | LENGTH | TOOTH PITCH |
|-------|--------|-------------|
| 765mm | 965mm  | 30mm        |

## PRODUCT APPLICATIONS

- Demolition work, construction work, civil engineering, road work, mining, dredging, rock work, municipal waste disposal, recycling and reuse and other fields of crushing work.
- The crushing and recycling of construction waste such as concrete, bricks, asphalt concrete, ceramics, glass, etc.
- Crushing work of railway cement sleepers, cement poles, various bridge pier piles, etc.
- Pavement construction and earthwork, excavation engineering, forest road construction site crushing and processing of aggregates, etc.
- The processing of natural stone in quarries, mines, gravel pits, river pebble pits, etc.
- Sand making (using Yichen's special fine-tooth jaws) to meet the needs of construction materials in areas lacking sand.

## PRODUCT PARAMETER (SPECIFICATION)

|                |           |                |                    |
|----------------|-----------|----------------|--------------------|
| Excavator      | 25-40 ton | Output Setting | 10- 120 mm         |
| Inlet opening  | 800*860   | Load Capacity  | 1.1 m <sup>3</sup> |
| Rated Oil Flow | 160 lpm   | Dimensions     | 1959x1146x1218 mm  |
| Rated Pressure | 250 bar   | Weight         | 2750 kgs           |



## APPLICATIONS



Jobsite



Quarries



Roadworks



Sand Production



Demolition



Recycling

\*The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.