



# YF-02RW

YF-02RW	YF-15RW	YF-40RW
YF-05RW	YF-20RW	YF-50RW
YF-10RW	YF-30RW	YF-60RW



## EXCAVATOR

# 0.7-2.5 ton

## PRODUCT APPLICATIONS

- Tunnels and roadways: excavation and treatment of walls, roofs, corners, contours, trenches, etc.;
- Road engineering: cutting or excavation of concrete structures, side trenches, slopes and auxiliary facilities, cleaning of damaged cement or asphalt pavements, etc.;
- Water conservancy project: concrete structure treatment, riverbed cleaning, cleaning or dismantling of damaged structures, etc.;
- Municipal engineering: excavation or treatment of pipeline trenches, foundations, structures, cleaning or dismantling of damaged municipal facilities, etc.;
- Open-pit coal mining: excavation and mining of coal mines and mines, etc.

## PRODUCT PARAMETER (SPECIFICATION)

Max Power Output	16 kW	Output Torque	1592 Nm@315bar
Max Flow	45 LPM	Output Shaft Speed	100 RPM@40LPM
Recommended Flow	20-40 LPM	Weight	145 kgs
Max Pressure	315 bar	Cutter Bit	44 pcs

**Note:** If oil specification is below 46 centistokes at 40 C (ISO HV46) the performance must be down rated.  
Please contact YICHEN for further information.



## APPLICATIONS



Tunneling



Utility Work



Roadworks



Mining



Excavation



Structure-Shaping

\*The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.