



YS-10SS

YS-30DS YS-20SS YS-05SS
YS-20DS YS-15SS YS-02SS
YS-25SS **YS-10SS**



EXCAVATOR

8-16 ton

PRODUCT APPLICATIONS

- Building demolition, cutting reinforced concrete, cement pavement, highway construction and maintenance operations.
- Crushing operation after cutting hard rock.
- Excavation of foundation, rock and concrete of basement.
- Underground cable trench cutting operation.
- Quarry excavation operations, rock waste reshaping, cutting and other operations.
- Rocky tunnel excavation, rocky trench excavation and other operations.

PRODUCT PARAMETER (SPECIFICATION)

Max Power Output	48 kW	Output Shaft Speed	0- 468 RPM
Max Flow	160 LPM	Weight	350 kgs
Recommended Flow	100- 150 LPM	Saw Blade spec.	Φ 1400- 2000 mm
Max Pressure	315 bar	Applicable Materials	granite, basalt, marble, reinforced concrete
Output Torque	1580 Nm@315bar		

Note: The rock saw can cut aluminum and reinforced concrete by changing different specifications of saw blades.
The rock saw can work with any hydraulic driven mechanical equipment.
The rock saw can install two saw blades at the same time(on the same side), the distance between the blades is 50-200mm. Saw blade cover can be installed 360° freely.



APPLICATIONS



Demolition



Tunneling



Stone Production



Roadworks



Quarries



Trenching



Metal cutting

*The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.